# AGRO cable glands Progress® nickel-plated brass with clamps increased safe




## Short entry thread Pg

**Type approval: Progress MS KB EX**

- Two-piece sealing insert
- not overall length insulated

| **Order number:** | **EX1803.48** |
|---|---|
| EAN: | 7611614177120 |
| Material | Nickel-plated brass |
| Screws | Stainless steel A2 |
| Seal | TPE |
| O-ring | FPM |
| Operation temperature | -60°C / +100°C |
| Protection class | IP 66 / IP 68 (up to 10 bar) |
| Test standard | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas | II 2G Ex eb IIC Gb |
| Dust | II 2D Ex tb IIIC Db |
| Zone | Gas 1 and 2 / dust 21 and 22 |
| Certificate | SEV 15 ATEX 0151 |
| IECEx Certificate | IECEx SEV 15.0018 |
| Entry thread | Pg 48 |
| Clamping range with insert min. | 37.0 mm |
| Clamping range with insert max. | 43.0 mm |
| Clamping range without insert min. | 43.0 mm |
| Clamping range without insert max. | 49.0 mm |
| Wrench size | 65 mm |
| Dimension H | 51 mm |
| Thread length L | 11 mm |
| Additional note | - |
| Dispatch | 5 |

1 = One-piece sealing insert
2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

**Available on request:**
- Long entry thread
- Executions in steel A2 and A4



Data weryfikacji 07.10.2025 | Dystrybucja ASTAT