

## Cable glands Progress® EMC nickel-plated brass with contact sleeve



### Long entry thread metric

#### Type approval: Progress MS EMV

- One-piece sealing insert
- not overall length insulated

|                                    |                                                                                                                    |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Order number:</b>               | <b>1180.40.285</b>                                                                                                 |
| E-No:                              | 121032708                                                                                                          |
| EAN:                               | 7611614119588                                                                                                      |
| Material                           | Nickel-plated brass                                                                                                |
| Contact sleeve                     | Nickel-plated brass                                                                                                |
| Seal                               | TPE                                                                                                                |
| O-ring                             | NBR                                                                                                                |
| Operation temperature              | -40°C / +100°C                                                                                                     |
| Strain relief                      | Version A acc. to EN 62444                                                                                         |
| Protection class                   | IP 68 (up to 10 bar) / IP 69                                                                                       |
| NEMA Type rating                   | 4X                                                                                                                 |
| Properties                         | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread                       | M40x1.5                                                                                                            |
| Clamping range without insert min. | 24.0 mm                                                                                                            |
| Clamping range without insert max. | 28.5 mm                                                                                                            |
| Wrench size                        | 46 mm                                                                                                              |
| Dimension H                        | 34 mm                                                                                                              |
| Thread length L                    | 13 mm                                                                                                              |
| Dispatch                           | 10                                                                                                                 |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.