


Cable glands Progress® EMC easyCONNECT nickel-plated brass with contact



Short entry thread metric

Type approval: Progress EMV easyCONNECT

- Two-piece sealing insert
- not overall length insulated

| | |
|------------------------------------|--|
| Order number: | 1083.12.050 |
| E-No: | 121062408 |
| EAN: | 7611614249698 |
| Material | Nickel-plated brass |
| Contact spring | Spring steel 1.4310 |
| Seal | TPE |
| O-ring | NBR |
| Operation temperature | -60°C / +100°C |
| Strain relief | Version A acc. to EN 62444 |
| Protection class | IP 68 (up to 10 bar) / IP 69 |
| NEMA Type rating | 4X |
| Properties | For a quick and safe installation of partially dismantled cables as well as thoroughly shielded cables |
| Entry thread | M12x1.5 |
| Clamping range with insert min. | - mm |
| Clamping range with insert max. | - mm |
| Clamping range without insert min. | 3.5 mm |
| Clamping range without insert max. | 5.0 mm |
| Wrench size | 15 mm |
| Dimension H | 22 mm |
| Thread length L | 5 mm |
| Additional note | 1 |
| Dispatch | 50 |

1 = One-piece sealing insert

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

Available on request:

- Entry thread Pg and NPT
- Executions in steel A2 and A4