


## Cable glands Progress® EMC Rapid nickel-plated brass with contact disc



### Long entry thread Pg

#### Type approval: Progress MS EMV Rapid

- One-piece sealing insert
- not overall length insulated

|                                    |                                                                                               |
|------------------------------------|-----------------------------------------------------------------------------------------------|
| <b>Order number:</b>               | <b>1181.11.120</b>                                                                            |
| EAN:                               | 7611614207384                                                                                 |
| Material                           | Nickel-plated brass                                                                           |
| Contact sleeve                     | Nickel-plated brass                                                                           |
| Contact disc                       | Stainless steel A2                                                                            |
| Seal                               | TPE                                                                                           |
| O-ring                             | NBR                                                                                           |
| Operation temperature              | -40°C / +100°C                                                                                |
| Protection class                   | IP 68 (up to 10 bar) / IP 69                                                                  |
| NEMA Type rating                   | 4X                                                                                            |
| Properties                         | For a quick installation of partially dismantled cables as well as thoroughly shielded cables |
| Entry thread                       | Pg 11                                                                                         |
| Clamping range without insert min. | 8.5 mm                                                                                        |
| Clamping range without insert max. | 12.0 mm                                                                                       |
| Wrench size                        | 21 mm                                                                                         |
| Dimension H                        | 25 mm                                                                                         |
| Thread length L                    | 10 mm                                                                                         |
| Dispatch                           | 50                                                                                            |