


## Cable glands Progress® nickel-plated brass



### Short entry thread metric

#### Type approval: Progress MS

- One-piece sealing insert
- overall length insulated

|                                    |                              |
|------------------------------------|------------------------------|
| <b>Order number:</b>               | <b>1060.06.025</b>           |
| E-No:                              | 121077008                    |
| EAN:                               | 7611614105086                |
| Material                           | Nickel-plated brass          |
| Seal                               | TPE                          |
| O-ring                             | NBR                          |
| Operation temperature              | -40°C / +100°C               |
| Strain relief                      | Version A acc. to EN 62444   |
| Protection class                   | IP 68 (up to 10 bar) / IP 69 |
| NEMA Type rating                   | 4X                           |
| Entry thread                       | M6x1.0                       |
| Clamping range without insert min. | 2.0 mm                       |
| Clamping range without insert max. | 2.5 mm                       |
| Wrench size                        | 8 mm                         |
| Dimension H                        | 12 mm                        |
| Thread length L                    | 5 mm                         |
| Note                               | 1                            |
| UL - clamping range                | 2.5-2.5 mm                   |
| Dispatch                           | 50                           |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.