


## Cable glands Progress® nickel-plated brass elbow 90°



### Long entry thread metric with lock nut

#### Type approval: Progress MS W90

- Two-piece sealing insert
- not overall length insulated

|                                    |                            |
|------------------------------------|----------------------------|
| <b>Order number:</b>               | <b>5215.25</b>             |
| E-No:                              | 121521608                  |
| EAN:                               | 7611614133416              |
| Material                           | Nickel-plated brass        |
| Seal                               | TPE                        |
| O-ring                             | NBR                        |
| Operation temperature              | -40°C / +100°C             |
| Strain relief                      | Version A acc. to EN 62444 |
| Protection class                   | IP 68                      |
| Entry thread                       | M25x1.5                    |
| Clamping range with insert min.    | 12.5 mm                    |
| Clamping range with insert max.    | 16.0 mm                    |
| Clamping range without insert min. | 16.0 mm                    |
| Clamping range without insert max. | 20.5 mm                    |
| Wrench size                        | 30 mm                      |
| Dimension H                        | 48 mm                      |
| Thread length L                    | 14 mm                      |
| Dimension A                        | 20 mm                      |
| Dimension B                        | 52 mm                      |
| Note                               | -                          |
| Dispatch                           | 25                         |

1 = One-piece sealing insert

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.