


## Cable glands Progress® nickel-plated brass with antikink spring



### Short entry thread metric

#### Type approval: Progress MS FKN

- One-piece sealing insert
- overall length insulated

|                                    |                              |
|------------------------------------|------------------------------|
| <b>Order number:</b>               | <b>1060.20.52.145</b>        |
| E-No:                              | 121783528                    |
| EAN:                               | 7611614195186                |
| Material                           | Nickel-plated brass          |
| Antikink spring                    | Stainless steel A2           |
| Seal                               | TPE                          |
| O-ring                             | NBR                          |
| Operation temperature              | -40°C / +100°C               |
| Strain relief                      | Version A acc. to EN 62444   |
| Protection class                   | IP 68 (up to 10 bar) / IP 69 |
| Entry thread                       | M20x1.5                      |
| Clamping range without insert min. | 11.0 mm                      |
| Clamping range without insert max. | 14.5 mm                      |
| Wrench size                        | 24 mm                        |
| Dimension H                        | 86 mm                        |
| Thread length L                    | 6 mm                         |
| Dispatch                           | 10                           |

1 = Metric coarse-pitch thread (with VDE test report)

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.

#### Available on request:

- Short entry thread with short one-piece or two-piece sealing insert.
- Long entry thread with short or full-length insulating one-piece or two-piece sealing insert.