


## AGRO cable glands Progress® nickel-plated brass with clamps increased safe

**Short entry thread Pg****Type approval: Progress MS KB EX**

- Two-piece sealing insert
- not overall length insulated

|                                    |                                                   |
|------------------------------------|---------------------------------------------------|
| <b>Order number:</b>               | <b>EX1803.07.03.065</b>                           |
| EAN:                               | 7611614176666                                     |
| Material                           | Nickel-plated brass                               |
| Screws                             | Stainless steel A2                                |
| Seal                               | TPE                                               |
| O-ring                             | FPM                                               |
| Operation temperature              | -60°C / +100°C                                    |
| Protection class                   | IP 66 / IP 68 (up to 10 bar)                      |
| Test standard                      | IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31 |
| Gas                                | II 2G Ex eb IIC Gb                                |
| Dust                               | II 2D Ex tb IIIC Db                               |
| Zone                               | Gas 1 and 2 / dust 21 and 22                      |
| Certificate                        | SEV 15 ATEX 0151                                  |
| IECEx Certificate                  | IECEx SEV 15.0018                                 |
| Entry thread                       | Pg 7                                              |
| Clamping range with insert min.    | - mm                                              |
| Clamping range with insert max.    | - mm                                              |
| Clamping range without insert min. | 5.0 mm                                            |
| Clamping range without insert max. | 6.5 mm                                            |
| Wrench size                        | 15/16 mm                                          |
| Dimension H                        | 26 mm                                             |
| Thread length L                    | 6 mm                                              |
| Additional note                    | 1/2                                               |
| Dispatch                           | 50                                                |

1 = One-piece sealing insert

2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

**Available on request:**

- Long entry thread
- Executions in steel A2 and A4