


AGRO cable glands Progress® nickel-plated brass with clamps increased safe

**Short entry thread Pg****Type approval: Progress MS KB EX**

- Two-piece sealing insert
- not overall length insulated

Order number:	EX1803.07.03.080
EAN:	7611614176680
Material	Nickel-plated brass
Screws	Stainless steel A2
Seal	TPE
O-ring	FPM
Operation temperature	-60°C / +100°C
Protection class	IP 66 / IP 68 (up to 10 bar)
Test standard	IEC EN 60079-0 / IEC EN 60079-7 / IEC EN 60079-31
Gas	II 2G Ex eb IIC Gb
Dust	II 2D Ex tb IIIC Db
Zone	Gas 1 and 2 / dust 21 and 22
Certificate	SEV 15 ATEX 0151
IECEx Certificate	IECEx SEV 15.0018
Entry thread	Pg 7
Clamping range with insert min.	- mm
Clamping range with insert max.	- mm
Clamping range without insert min.	6.5 mm
Clamping range without insert max.	8.0 mm
Wrench size	15/16 mm
Dimension H	26 mm
Thread length L	6 mm
Additional note	1/2
Dispatch	50

1 = One-piece sealing insert

2 = Certificate SEV 15 ATEX 0152X / IECEx SEV 15.0019X

Available on request:

- Long entry thread
- Executions in steel A2 and A4