

## Cable glands Progress® EMC nickel-plated brass with contact sleeve for high

**Long entry thread Pg**

- One-piece sealing insert
- not overall length insulated

|                                    |                                                                                                                    |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------|
| <b>Order number:</b>               | <b>1180.21.91.160</b>                                                                                              |
| EAN:                               | 7611614233796                                                                                                      |
| Material                           | Nickel-plated brass                                                                                                |
| Contact sleeve                     | Nickel-plated brass                                                                                                |
| Seal                               | FPM                                                                                                                |
| O-ring                             | FPM                                                                                                                |
| Operation temperature              | -40°C / +200°C                                                                                                     |
| Protection class                   | IP 68 (up to 10 bar) / IP 69                                                                                       |
| Properties                         | Excellent shield contact through the contact sleeve with the braided shield terminating in the screwed cable gland |
| Entry thread                       | Pg 21                                                                                                              |
| Clamping range without insert min. | 13.0 mm                                                                                                            |
| Clamping range without insert max. | 16.0 mm                                                                                                            |
| Wrench size                        | 30 mm                                                                                                              |
| Dimension H                        | 30 mm                                                                                                              |
| Thread length L                    | 12 mm                                                                                                              |
| Dispatch                           | 25                                                                                                                 |