


## Cable glands Progress® nickel-plated brass with trumpet



### Short entry thread metric

#### Type approval: Progress MS T

- Two-piece sealing insert
- not overall length insulated

|                                    |                              |
|------------------------------------|------------------------------|
| <b>Order number:</b>               | <b>1800.10.20</b>            |
| E-No:                              | 121401508                    |
| EAN:                               | 7611614127163                |
| Material                           | Nickel-plated brass          |
| Seal                               | TPE                          |
| O-ring                             | NBR                          |
| Operation temperature              | -40°C / +100°C               |
| Strain relief                      | Version A acc. to EN 62444   |
| Protection class                   | IP 68 (up to 10 bar) / IP 69 |
| Entry thread                       | M20x1.5                      |
| Clamping range with insert min.    | 8.0 mm                       |
| Clamping range with insert max.    | 11.0 mm                      |
| Clamping range without insert min. | 11.0 mm                      |
| Clamping range without insert max. | 15.0 mm                      |
| Wrench size                        | 24 mm                        |
| Diameter A                         | 34                           |
| Dimension H                        | 32 mm                        |
| Thread length L                    | 6 mm                         |
| Dispatch                           | 50                           |

Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.