


## Short entry thread metric

**AGRO combination conduit glands Progress® nickel-plated brass with integrated cable gland****Type approval: Progress MS Kombi**

- Connector for tubing with AD mm
- Two-piece sealing insert
- not overall length insulated

|                                    |                                                               |
|------------------------------------|---------------------------------------------------------------|
| <b>Order number:</b>               | <b>1700.20.17</b>                                             |
| E-No:                              | 126648500                                                     |
| EAN:                               | 7611614143910                                                 |
| Material                           | Nickel-plated brass                                           |
| Seal                               | TPE                                                           |
| O-ring                             | NBR                                                           |
| Operation temperature              | -40°C / +100°C                                                |
| Strain relief                      | Version A acc. to EN 62444                                    |
| Protection class                   | Cable gland IP 68                                             |
| Note                               | The max. clamping range depends on the conduit inner diameter |
| Entry thread                       | M20x1.5                                                       |
| Outer diameter                     | 17 mm                                                         |
| Clamping range with insert min.    | 8.0 mm                                                        |
| Clamping range with insert max.    | 11.0 mm                                                       |
| Clamping range without insert min. | 11.0 mm                                                       |
| Clamping range without insert max. | 15.0 mm                                                       |
| Wrench size                        | 24/25 mm                                                      |
| Dimension H                        | 38 mm                                                         |
| Thread length L                    | 6 mm                                                          |
| Dispatch                           | 25                                                            |

Depending on the type of conduit, the stabilising bush must be ordered separately.  
Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.