


## Synthetic straight conduit connector



### Synthetic straight conduit connector

- Quick connector RQG-M
- Grey

|                       |                                                                                                                           |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------|
| <b>Order number:</b>  | <b>5020.037.012</b>                                                                                                       |
| E-No:                 | 126807300                                                                                                                 |
| EAN:                  | 7611614094984                                                                                                             |
| Material              | Polyamide impact-resistant                                                                                                |
| Seal                  | TPE                                                                                                                       |
| Fire classification   | V0 (UL 94)                                                                                                                |
| Properties            | Quick and pull-out-proof installation by means of the «push-in» lock, simple dismounting by displacing the snap-in sleeve |
| Protection class      | IP 68 / IP 69                                                                                                             |
| Operation temperature | -40°C / +120°C                                                                                                            |
| Outer diameter        | 13.0 mm                                                                                                                   |
| Entry thread          | M12x1.5                                                                                                                   |
| Diameter Ø I          | 7.0 mm                                                                                                                    |
| Diameter Ø B          | 20.0 mm                                                                                                                   |
| Dimension C           | 12.0 mm                                                                                                                   |
| Dimension D           | 37.0 mm                                                                                                                   |
| Wrench size           | 18 mm                                                                                                                     |
| Dispatch              | 50                                                                                                                        |