





PUSH BUTTON STATION ENCLOSURES | IP65



	TYPE	COVER COLOUR	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
	1 HOLES ENCLOSURE	■	PQ01K	134	1	
		■	PQ01KGN			


	TYPE	COVER COLOUR	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
	2 HOLES ENCLOSURE	■	PQ02K	174	1	
		■	PQ02KGN			

	TYPE	COVER COLOUR	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
	3 HOLES ENCLOSURE	■	PQ03K	214	1	
		■	PQ03KGN			

	TYPE	COVER COLOUR	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
	4 HOLES ENCLOSURE	■	PQ04K	256	1	
		■	PQ04KGN			

PUSH BUTTON STATION ENCLOSURES | IP65

	TYPE	COVER COLOUR	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
	5 HOLES ENCLOSURE	■	PQ05K	296	1	
		■	PQ05KGN			

	TYPE	COVER COLOUR	CODE	WEIGHT grams	MIN. PACK QUANTITY	SIZES
	6 HOLES ENCLOSURE	■	PQ06K	386	1	
		■	PQ06KGN			

CHARACTERISTICS

- ABS self-extinguishing material.
- Self-extinguishing class V0 UL94.
- EN60529 IP65 protection grade.
- Double insulation □.
- Colors: Black box; Yellow cover; Grey cover.
- Threaded cable entry with membrane conduit knock:
 - 1 hole box nr. 1 M16 + 1 M20 gland, from 2 to 5 holes nr. 2 M20 glands;
 - 6 holes nr. 1 M20 + 1 M25 glands

ASSEMBLING

