

PLATEO 4

SLI044029CW_PW

PLATEO 4 HIGH BAY 200W / 150W / 100W CW 230V 90DEG IP65 IK09 280X145MM BLACK 5Y WARRANTY WITH POWER CHANGE 0-10V



Power	100 / 150 / 200 W	Voltage	230 V
Luminous flux*	31000 lm (360°)	Colour temperature	6500 K
Colour of light	CW	Beam angle	90 °
IK	9	Degree of protection (IP)	IP65

Technical data

Code	SLI044029CW_PW
Power	100 / 150 / 200 W
Nominal current	900 mA
Voltage	230 V
Energy consumption	200 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.97
Useful luminous flux*	31000 lm (360°)
Luminous flux**	15000-23000-30000 lm (360°)
Lamp efficacy	155 lm/W
Luminous intensity	13500 cd
Colour temperature	6500 K
Colour of light	CW
Beam angle	90 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	0-10V
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
Housing material	Aluminum, PC
IK	9
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	280x145 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT / EXT
Made in	PRC

Logistics data

Quantity per pallet	100 pcs.
Gross weight (1 pcs.)	2.3 kg



Related documents

 User manual

