

MOBILO LED CCT

SLI043040CCT_PW

MOBILO LED 6.5W CCT 230V 36DEG. IP20 F1105x35MM BLACK ROUND



Power	6,5 W	Voltage	230 V
Luminous flux*	850 lm (360°)	Colour temperature	2700 / 4000 / 6000 K
Colour of light	CCT	Beam angle	36 °
Degree of protection (IP)	IP20		

Technical data


Code	SLI043040CCT_PW
Power	6,5 W
Nominal current	52 mA
Voltage	230 V
Energy consumption	7 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0,5
Useful luminous flux*	850 lm (360°)
Luminous flux**	800 lm (360°)
Lamp efficacy	130 lm/W
Luminous intensity	1300 cd
Colour temperature	2700 / 4000 / 6000 K
Colour of light	CCT
Beam angle	36 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
Housing material	PC+PS
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	105x35 mm
Mounting hole	90 mm
For use	Inside
Assembly method	Recessed
Application	INT
Made in	PRC
Other	Light color change function 2700K / 4000K / 6000K ,

Logistics data


Bulk packaging	20 pcs.
Gross weight (1 pcs.)	0.29 kg

Related documents



 User manual



 Declaration of Conformity