

# LIMEA PRISMATICA

SLI028036CCT\_PW

LIMEA PRISMATICA 1200mm 40W / 30W / 20W 3CCT 230V 100deg IP44 IK10 1200x115x60mm 5 years warranty




Power	<b>20 / 30 / 40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5200 lm (360°)</b>	Colour temperature	<b>3000 / 4000 / 6000 K</b>
Colour of light	<b>CCT</b>	Beam angle	<b>100 °</b>
UGR	<b>22</b>	IK	<b>10</b>

## Technical data

Code	SLI028036CCT_PW
Power	20 / 30 / 40 W
Nominal current	185 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.95
Useful luminous flux*	5200 lm (360°)
Luminous flux**	2600 / 3600 / 4600 lm (360°)
Lamp efficacy	130 lm/W
Luminous intensity	2000 cd
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	100 °
UGR	22
RA	>80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum / PC
IK	10
Degree of protection (IP)	IP44
Colour	White
Dimension (AxBxC)	1200x115x60 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	INTERNAL
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	Regulacja 3000K / 4000K / 6000K i 30W / 40W / 50W ,

## Logistics data

Bulk packaging	10 pcs.
Gross weight (1 pcs.)	1.59 kg



## Related documents



 User manual



 Declaration of Conformity

