

PLATEO 4

SLI044034NW_PW

PLATEO 4 HIGH BAY 100W/75W/55W NW 230V 90DEG IP65 IK09 220X135MM BLACK 5Y WARRANTY WITH POWER CHANGE 0-10V



Power	55/75/100 W	Voltage	230 V
Luminous flux*	16000 lm (360°)	Colour temperature	4000 K
Colour of light	Neutral white	Beam angle	90 °
IK	9	Degree of protection (IP)	IP65

Technical data

Logistics data

Code	SLI044034NW_PW
Power	55/75/100 W
Nominal current	460 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.950000
Useful luminous flux*	16000 lm (360°)
Luminous flux	8250/11250/15000 lm (360°)
Lamp efficacy	160 lm/W
Luminous intensity	6500 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	90 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	0-10V
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum, PC
IK	9
Degree of protection (IP)	IP65
Colour	Black
Dimension (AxBxC)	220x135 mm
For use	Inside/Outside
Assembly method	Suspended
Application	INT/EXT
Made in	PRC

*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity