

SLI035090WW_PW

ALGINE PANEL BACKLIGHT 40W WW 230V 90DEG IP40 UGR19 RA90 600X600X28 WHITE 5Y WARRNTY



Power	40 W	Voltage	230 V
Luminous flux*	4800 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	90 °
UGR	<19	Degree of protection (IP)	IP40

Technical data

Logistics data

Code	SLI035090WW_PW
Power	40 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.970000
Useful luminous flux*	4800 lm (360°)
Luminous flux	4400 lm (360°)
Lamp efficacy	120 lm/W
Colour temperature	3000 K
Colour of light	WW
Beam angle	90 °
UGR	<19
RA	90
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum/Steel/Plastic
Degree of protection (IP)	IP40
Colour	White
Dimension (AxBxC)	595x595x28 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	montaż ramka 70 mm lub sufit armstrong ,

Bulk packaging 10 pcs.

*applies to the LED source used