

# SLI035091CW\_PW

ALGINE PANEL BACKLIGHT 40W CW 230V 90DEG IP40 UGR19 RA90 300X1200X28 WHITE 5Y WARRANTY



Power	<b>40 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>5200 lm (360°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>90 °</b>
UGR	<b>&lt;19</b>	Degree of protection (IP)	<b>IP40</b>

## Technical data

## Logistics data

Code	SLI035091CW_PW
Power	40 W
Nominal current	175 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.970000
Useful luminous flux*	5200 lm (360°)
Luminous flux	4800 lm (360°)
Lamp efficacy	130 lm/W
Colour temperature	6000 K
Colour of light	CW
Beam angle	90 °
UGR	<19
RA	90
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum/Steel/Plastic
Degree of protection (IP)	IP40
Colour	White
Dimension (AxBxC)	295x1195x28 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	montaż ramka 70 mm ,

Bulk packaging 10 pcs.

\*applies to the LED source used