

NYMPHEA SELECT CCT

SLI031060CCT_PW

NYMPHEA SELECT 24W/35W/40W CCT 230V 120DEG IP20 400X400X33MM BLACK 5Y WARRANTY



Power	24/35/40 W	Voltage	230 V
Luminous flux*	4650 lm (360°)	Colour temperature	3000/4000/6000 K
Colour of light	CCT	Beam angle	120 °
Degree of protection (IP)	IP20		

Technical data

Code	SLI031060CCT_PW
Power	24/35/40 W
Nominal current	180 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.960000
Useful luminous flux*	4650 lm (360°)
Luminous flux	1920/2800/3200 lm (360°)
Lamp efficacy	116 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	120 °
RA	80
Light source included	+
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum/PP
Degree of protection (IP)	IP20
Colour	Black
Dimension (AxBxC)	400x400x33 mm
For use	Inside
Assembly method	On the ceiling, Suspended
Application	Inside
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,


Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	120 pcs.
Gross weight (1 pcs.)	0.8 kg


*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity