

ALGINE LINE CCT

SLI035050CCT_PW

ALGINE LINE PANEL 40W 3CCT 230V 80DEG IP20 600x600x15MM WHITE UGR16 5Y WARRANTY



Power	40 W	Voltage	230 V
Luminous flux*	4650 lm (360°)	Colour temperature	3000/4000/6000 K
Colour of light	CCT	Beam angle	80 °
UGR	<16	Degree of protection (IP)	IP20

Technical data

Logistics data

Code	SLI035050CCT_PW
Power	40 W
Nominal current	180 mA
Voltage	230 V
Energy consumption	40 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	+
Power factor	0.970000
Useful luminous flux*	4650 lm (360°)
Luminous flux	4000 lm (360°)
Lamp efficacy	116 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	80 °
UGR	<16
RA	>80
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Steel/PC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	595x595x15 mm
Mounting hole	565x565 mm
For use	Inside
Assembly method	On the ceiling, Recessed
Application	INT
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	Funkcja CCT ,

Bulk packaging	8 pcs.
Gross weight (1 pcs.)	3.35 kg

*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity