

SLI033043WW_PW

ANDROMEDA 24-30W WW 230V 36, 60deg IP20 RA90 74x170x170 WHITE 5Y WARRANTY POWER ADJUSTABLE



Power	24-30 W	Voltage	230 V
Colour temperature	3000 K	Colour of light	WW
Beam angle	36, 60 °	Degree of protection (IP)	IP20

Technical data

Code	SLI033043WW_PW
Power	24-30 W
Nominal current	134 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.960000
Useful luminous flux*	3300 lm (360°)
Luminous flux	2500-3000 lm (360°)
Lamp efficacy	110 lm/W
Luminous intensity	7500 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	36, 60 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	74x170x223 mm
For use	Inside
Assembly method	on track 3-fazowy
Application	Inside
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,


Logistics data

Bulk packaging	24 pcs.
Gross weight (1 pcs.)	0.67 kg

*applies to the LED source used

Related documents



 User manual

