

# SLI033043NW\_PW

ANDROMEDA 24-30W NW 230V 36, 60deg IP20 Ra90 74x170x170 WHITE 5Y WARRANTY POWER ADJUSTABLE



Power	<b>24-30 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>4000 K</b>	Colour of light	<b>Neutral white</b>
Beam angle	<b>36, 60 °</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data

---


Code	SLI033043NW_PW
Power	24-30 W
Nominal current	134 mA
Voltage	230 V
Energy consumption	30 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.960000
Useful luminous flux*	3300 lm (360°)
Luminous flux	2500-3000 lm (360°)
Lamp efficacy	110 lm/W
Luminous intensity	7500 cd
Colour temperature	4000 K
Colour of light	Neutral white
Beam angle	36, 60 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	Aluminum, PLASTIC
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	74x170x223 mm
For use	Inside
Assembly method	on track 3-fazowy
Application	Inside
Made in	PRC
Other	DIP SWITCH - adjustable power of luminaire ,

\*applies to the LED source used

## Related documents

---



 User manual

