

Technical data sheet

External corner hood, for device installation trunking Rapid 45-2 type GK-53100
Item number: 6113053



External corner for changing the direction of Rapid 45-2 device installation trunking. The fittings can be adjusted between 80–110°.



Polycarbonate/Acrylnitrile-butadiene-styrene

Master data

| | |
|------------------------------------|--|
| Item number | 6113053 |
| Type | GK-AH53100SW |
| Description 1 | External corner |
| Description 2 | variable |
| Manufacturer | OBO |
| Dimension | 110x88x88 |
| Colour | Jet black; RAL 9005 |
| Material | Polycarbonate/Acrylnitrile-butadiene-styrene |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 7.153 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 0,6104 kg CO2e / 1 Piece |

Dimensions

| | |
|--------|--------|
| Length | 88 mm |
| Width | 110 mm |
| Height | 55 mm |

Technical data sheet

External corner hood, for device installation trunking Rapid
45-2 type GK-53100
Item number: 6113053



Technical data

| | |
|--------------------------------------|--------------|
| Number of covers | 1 |
| Version for | Hood fitting |
| for duct width | 100 mm |
| for trunking height | 53 mm |
| Halogen-free | yes |
| Cable retaining clip | no |
| Duct connector | no |
| Cover mounting type | Cross-over |
| Mounting perforation in base | no |
| Cover width | 0 mm |
| Cover width 2 | 0 mm |
| Cover width 3 | 0 mm |
| Protective film | no |
| Symmetrical | yes |
| Permitted temperature range, max. | 60 °C |
| Permitted temperature range, min. | -5 °C |
| Angle range, max. | 110 mm |
| Angle range, min. | 80 mm |