


Technical data sheet

Cable tray, marine standard, ALU

Item number: 6045707



Cable tray for use in ship construction, produced according to the marine standard VG 88900-1.



Alu Aluminium

Master data

Item number	6045707
Type	MKR 15 050 ALU
Description 1	Cable tray marine standard
Description 2	Material thickness 1.50mm
Manufacturer	OBO
Dimension	15x50x2000
Colour	aluminium
Material	Aluminium
Smallest sales unit	2
Unit of quantity	Metre
Weight	25.5 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	4,7154 kg CO2e / 1 Meter


Technical data sheet

Cable tray, marine standard, ALU



Item number: 6045707

Dimensions



Dimension	15 x 50
Length	2,000 mm
Width	50 mm
Height	15 mm
Plate thickness	1.5 mm
Dimension B	50 mm

Technical data

Connector version	Without connectors
Walkable	no
Maintain electrical functions	no
With cover	no
Mounting perforation in base	yes
NATO hole pattern	yes
Rustproof steel, pickled	no
Side perforation	no
Wide-span version	no
Load test type according to IEC 61537	Type II
Type of connector, cable support system	Screwed

Loads

Support spacing 1.0 m	0.3 kN/m
Support spacing 1.5 m	0.05 kN/m