

Technical data sheet

External corner, asymmetrical, for device installation trunking Rapid 80 type GS-A70130
Item number: 6277410



External corner for changing the direction of the GS device installation trunking.



St Steel

Master data	
Item number	6277410
Type	GS-AA70130RW
Description 1	External corner
Description 2	asymmetrical
Manufacturer	OBO
Dimension	70x130x300
Colour	Pure white; RAL 9010
Material	Steel
Smallest sales unit	1
Unit of quantity	Piece
Weight	193 kg
Weight unit	kg/100 pc.
CO2 Footprint (GWP) Cradle-to-Gate	7,2342 kg CO2e / 1 Piece

Technical data sheet

External corner, asymmetrical, for device installation trunking Rapid 80 type GS-A70130


Item number: 6277410



Dimensions



Length	300 mm
Width	130 mm
Height	70 mm



Technical data

Number of covers	1
Version for	Base
for duct width	130 mm
for trunking height	70 mm
Halogen-free	yes
Cable retaining clip	no
Duct connector	no
Cover mounting type	Internal
Mounting perforation in base	yes
Cover width	76.5 mm
Protection rating	IP30
Protective film	yes
Protection rating IK code	IK10
Symmetrical	no
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-25 °C
Angle range, min.	90 mm