

Technical data sheet

Trunking, type WDKH 10020

Item number: 6175377



Duct cover and base with base perforation made of halogen-free plastic. With self-adhesive film for fastening on the underside. During installation, ensure that only halogen-free accessories and fastening materials are used.



PC/ABS Polycarbonate/Acrylnitrile-butadiene-styrene

Master data

Item number	6175377
Type	WDKH-10020RW T
Description 1	Wall trunking system
Description 2	halogen-free
Manufacturer	OBO
Dimension	10x20x2000
Colour	Pure white; RAL 9010
Material	Polycarbonate/Acrylnitrile-butadiene-styrene
Smallest sales unit	84
Unit of quantity	Metre
Weight	9.5 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	0,7374 kg CO2e / 1 Meter

Dimensions

Length	2,000 mm
Width	20 mm
Height	10 mm

Technical data sheet

Trunking, type WDKH 10020

Item number: 6175377



Technical data

Number of fixed partitions	0
Number of insertable partitions	0
Version, cable trunking cover	Loose
Fastening type	Base perforation
Base perforation	with base perforation
Halogen-free	yes
Cable retaining clip	yes
Duct connector	no
Usable cross-section	135 mm ²
Protection rating	IP30
Protective film	no
Protection rating IK code	IK07.
Permitted temperature range, max.	90 °C
Permitted temperature range, min.	-5 °C