

Technical data sheet

T and intersection cover, for trunking type WDKH 60110

Item number: 6176088



T and intersection cover for changing the direction of the halogen-free WDKH trunking. The fitting is preperforated at the side for the connection of different trunking cross-sections.



PC/ABS Polycarbonate/Acrylnitrile-butadiene-styrene

Master data

| | |
|------------------------------------|--|
| Item number | 6176088 |
| Type | WDKH-T60110LGR |
| Description 1 | T- and crosspiece cover |
| Description 2 | halogen-free |
| Manufacturer | OBO |
| Dimension | 60x110mm |
| Colour | Light grey; RAL 7035 |
| Material | Polycarbonate/Acrylnitrile-butadiene-styrene |
| Smallest sales unit | 2 |
| Unit of quantity | Piece |
| Weight | 20.921 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 1,2479 kg CO2e / 1 Piece |

Technical data sheet

T and intersection cover, for trunking type WDKH 60110

Item number: 6176088



Dimensions



| | |
|-------------|--------|
| Length | 272 mm |
| Width | 110 mm |
| Height | 60 mm |
| Dimension a | 272 mm |
| Dimension b | 114 mm |

Technical data

| | |
|-----------------------------------|--------------|
| Version for | Hood fitting |
| Fastening type | Lockable |
| Maintain electrical functions | no |
| for duct dimension | 60x |
| Halogen-free | yes |
| Trunking depth | 60 mm |
| Protection rating | IP30 |
| Protective film | no |
| Protection rating IK code | IK07. |
| Permitted temperature range, max. | 90 °C |
| Permitted temperature range, min. | -5 °C |