

Worklight 1500 lm, 4 light colors



Product description

Portable work lighting, which is characterised by very good quality of emitted light and high resistance to damage and durability. It is suitable for work in the most difficult conditions - construction, finishing, renovation, workshops and outdoors. High-quality LEDs shine with different intensity in selected 4 colours + red. This allows you to achieve 18 unique lighting conditions. The maximum distance of objects that can be illuminated is 60 m. The lamp is powered by an efficient battery, ensuring continuous operation for up to 17 hours. The housing made of aluminium, secured with rubber and ABS, with a high impact protection rating - IK07, guarantees full resistance to impact energy of 2 J, which is equivalent to an impact of a 500 g object from a height of 40 cm. Additionally, the housing is resistant to splashing water in IPX4 rating, which allows it to be safely used in light rain. It can work in a wide range of temperatures, outdoors in winter and in hot weather ranging from -20°C to +40°C. The handle working with a 360° tilt range allows the light to be directed in any direction. A strong magnet and a foldable hook for hanging make it possible to mount the floodlight anywhere and to free up hands for work. A socket with a 1/4" thread allows the floodlight to be mounted on a tripod. If necessary, it can work as a power bank and power other devices through Type A and Type C ports.

Characteristics

Max. luminous flux - 1,500 lm;

18 operating modes resulting from a mix of the following:

1. four colour temperatures - 6500 K., 4500 K., 3500 K., 2700 K.,
2. four light intensities - 20%, 40%, 60% and 100%,
3. red warning light with an operating time of 65 H,
4. red strobe light with an operating time of 100 H,

Operating time/ lighting intensity - 17 H/ 20%, 5 H/ 40%, 9 H/ 60%, 3 H/ 100%,

Light beam length/ lighting intensity: 60 m/100%,/45m/60%, 36m/40%, 24m/20%;

Impact protection class - IK07 (equivalent to an impact of a 500 g object from a height of 40 cm);

Waterproof class - IPX4 - protection against splashing water

Power supply - Li-Ion battery, 3.7 V, 8000 mAh;

Max. working time - 17 h;

Max. charging time - 6 h;

Head tilt adjustment - 360°;

Mounting - magnets, hook for hanging, 1/4" socket;

Charging port - USB-C, USB-A.

Technical data

			
HT1E431	5902801448591	1	20

Högert Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland

Producent/ Manufacturer/ Hersteller/ Произведено для:
PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków,
Polska/ Poland/ Polen/ Польша

Importer/ Импортёр:

01.2025

