

## PRODUCT INFORMATION SHEET

### Floodlight with tripod 10 000 lm



#### Product description

The floodlight, thanks to SMD LEDs, allows effective lighting of the workplace. The adjustment of arms makes it possible to control the angle of incidence of light, improving work comfort. Thanks to its water and dust resistance (IP54), the floodlight can be used wherever precise illumination of an object is required. Resistance to impact energy of 5 J (IK08) and temperature exposure guarantee lighting in particularly difficult conditions of renovation or construction works. The floodlight is equipped with an additional electrical socket, making it possible to connect additional devices without the need to use additional extension cords. A robust tripod provides stable access to light and lighting from any height, increasing work efficiency.

#### Characteristics

Luminous flux - 10,000 lm (2 x 5000 lm); Dust and water resistance - IP54; Impact protection class - IK08; LED type - SMD2835 x 56pcs; Cable length - 3 m; Operating temperature - from -25 to +45oC; Operating voltage - 100 – 240 V ~ 50/60 Hz; Colour temperature - 6500 K; Additional electrical socket – yes.

#### Technical data

			
HT1E455	5902801620485	1	2

Högert Technik GmbH, Pariser Platz 6a, 10117 Berlin, Deutschland

Producent/ Manufacturer/ Hersteller/ Произведено для:  
PL GTV Poland S.A., ul. Przejazdowa 21 05-800 Pruszków, Polska/ Poland/ Polen/ Польша

Importer/ Импортёр:

HR GTV Croatia d.o.o.; Kovinska 4s, 10000 Zagreb, Hrvatska

Distributor:

ES GTV España Herrajes, E Iluminación, S.L., Avenida Aragón 308, 46021 Valencia, Spain

CZ GTV Czech Distribution s.r.o., CTPark Ostrava, Na Rovince 879, 720 00 Ostrava Hrabová