

CRYSTAL LINE S

WLD+20130_MESH

CRYSTAL LINE SUSPENDED 623MM 12W 5Y WARRANTY MESH



Power	12 W	Voltage	230 V
Colour temperature	2200 / 3500 / 5500 K	Colour of light	CCT
Beam angle	45 °	UGR	<16
Degree of protection (IP)	IP20		

Technical data

Code	WLD+20130_MESH
Power	12 W
Nominal current	70 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	12 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.750000
Useful luminous flux*	1680 lm (360°)
Luminous flux	1080 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	2200 / 3500 / 5500 K
Colour of light	CCT
Beam angle	45 °
UGR	<16
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	MESH
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	30000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Szampańskie złoto
Dimension (AxBxC)	623x30x36 + baza 340x140x40 mm
For use	Inside
Assembly method	Suspended
Application	Inside
Made in	PL

*applies to the LED source used