

# CRYSTAL SPHERE M

WLD+20133\_CASAMBI

CRYSTAL SPHERE SUSPENDED 650MM 36W 5Y WARRANTY CASAMBI



Power	<b>36 W</b>	Voltage	<b>230 V</b>
Colour temperature	<b>2200-5500 K</b>	Colour of light	<b>CCT</b>
Beam angle	<b>45 °</b>	UGR	<b>&lt;16</b>
Degree of protection (IP)	<b>IP20</b>		

## Technical data

---

Code	WLD+20133_CASAMBI
Power	36 W
Nominal current	170 mA
Voltage	230 V
Energy efficiency class	E
Energy consumption	36 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	5040 lm (360°)
Luminous flux	3240 lm (360°)
Lamp efficacy	140 lm/W
Colour temperature	2200-5500 K
Colour of light	CCT
Beam angle	45 °
UGR	<16
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	CASAMBI
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	30000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Szampańskie złoto
Dimension (AxBxC)	650x36 + baza 300x40 mm
For use	Inside
Assembly method	Suspended
Application	Inside
Made in	PL

\*applies to the LED source used

