

DURE 3 CCT

SLI043010CCT_PW

DURE 3 DOWNLIGHT 12W CCT 230V 110DEG IP54 IK06 145X145X30 WHITE SQUARE



| | | | |
|---------------------------|-----------------------------|-----------------|--------------|
| Power | 12 W | Voltage | 230 V |
| Colour temperature | 3000 / 4000 / 6000 K | Colour of light | CCT |
| Beam angle | 110 ° | IK | 6 |
| Degree of protection (IP) | IP54 | | |

Technical data


Logistics data


| | |
|--|--|
| Code | SLI043010CCT_PW |
| Power | 12 W |
| Nominal current | 89 mA |
| Voltage | 230 V |
| Energy consumption | 12 kWh/1000h |
| Frequency | 50HZ Hz |
| Protection class | II |
| Power factor | 0.6 |
| Useful luminous flux* | 1500 lm (360°) |
| Luminous flux | 1000 lm (360°) |
| Lamp efficacy | 125 lm/W |
| Colour temperature | 3000 / 4000 / 6000 K |
| Colour of light | CCT |
| Beam angle | 110 ° |
| RA | 80 |
| Light source included | Yes |
| Uniformity of color SDCM max | 5 |
| Dimmable | No |
| Working temperature range | -20 / +40 ° |
| Warranty | 2 years |
| Lifespan | 17000 h |
| (On/Off) | 15000 |
| Housing material | PS |
| IK | 6 |
| Degree of protection (IP) | IP54 |
| Colour | White |
| Dimension (AxBxC) | 145x145x30 mm |
| Mounting hole | 125x125 mm |
| For use | Inside |
| Assembly method | Recessed |
| Application | INT |
| Certified by the National Institute of Hygiene | Yes |
| Made in | PRC |
| Other | Light color change function 3000K / 4000K / 6000K , |

Bulk packaging 60 pcs.

*applies to the LED source used

Related documents


 User manual

 Declaration of Conformity

