

DURE 3 CCT

SLI043009CCT_PW

DURE 3 DOWNLIGHT 24W CCT 230V 110DEG IP54 IK06 225X30 WHITE ROUND



Power	24 W	Voltage	230 V
Colour temperature	3000 / 4000 / 6000 K	Colour of light	CCT
Beam angle	110 °	IK	6
Degree of protection (IP)	IP54		

Technical data


Logistics data


Code	SLI043009CCT_PW
Power	24 W
Nominal current	174 mA
Voltage	230 V
Energy consumption	24 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power factor	0.6
Useful luminous flux*	2900 lm (360°)
Luminous flux	1900 lm (360°)
Lamp efficacy	121 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	110 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	2 years
Lifespan	17000 h
(On/Off)	15000
Housing material	PS
IK	6
Degree of protection (IP)	IP54
Colour	White
Dimension (AxBxC)	225x30 mm
Mounting hole	205 mm
For use	Inside
Assembly method	Recessed
Application	INT
Certified by the National Institute of Hygiene	Yes
Made in	PRC
Other	Light color change function 3000K / 4000K / 6000K ,

Bulk packaging 40 pcs.

*applies to the LED source used

Related documents


 User manual

 Declaration of Conformity

