

# NOCTIS MAX 2

SLI029078CW\_PW

Floodlight NOCTIS MAX 2, with a power of 100 W, high light efficacy 100 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a very high degree of protection IP65, providing protection against the ingress of dust and water jets. IK08 class provides impact resistance. It shines with a cold light (6000K). Narrow beam angle 85° gives directional light so that selected surfaces can be better exposed. Designed for surface mounting.



Power	<b>100 W</b>	Voltage	<b>230 V</b>
Luminous flux*	<b>10000 lm (120°)</b>	Colour temperature	<b>6000 K</b>
Colour of light	<b>CW</b>	Beam angle	<b>85 °</b>
IK	<b>08</b>	Degree of protection (IP)	<b>IP65</b>

## Technical data

Code	SLI029078CW_PW
Power	100 W
Nominal current	430 mA
Voltage	230 V
Energy consumption	100 kWh/1000h
Frequency	50HZ Hz
Protection class	I
Power factor	0.990000
Useful luminous flux*	10000 lm (120°)
Luminous flux	10000 lm (360°)
Lamp efficacy	100 lm/W
Luminous intensity	6000 cd
Colour temperature	6000 K
Colour of light	CW
Beam angle	85 °
RA	80
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
IK	08
Degree of protection (IP)	IP65
Colour	Szary
Dimension (AxBxC)	264x218x35 mm
For use	Outside
Assembly method	On the ceiling
Application	EXT


## Logistics data

Bulk packaging	10 pcs.
Quantity per pallet	300 pcs.
Gross weight (1 pcs.)	0.85 kg


\*applies to the LED source used

## Related documents



 User manual



 Declaration of Conformity



 Photometric file

