

ORBITO NATYNKOWA

SLI043037WW_PW

LED luminaire ORBITO NATYNKOWA, with a power of 10 W, high light efficacy 110 lm/W. It is made of high-quality components, supported by a 5-year warranty. It has a high IP44 rating, making it ideal for use in rooms with high humidity. It also stands out for its very high colour rendering index RA>90. It shines with a warm light (3000K), which promotes relaxation and rest, making the illuminated room cosier. Narrow beam angle 40° gives directional light so that selected objects or surfaces can be better exposed. Designed for surface mounting.



IP44

IK06



Power	10 W	Voltage	230 V
Luminous flux*	1100 lm (360°)	Colour temperature	3000 K
Colour of light	WW	Beam angle	40 °
UGR	<19	IK	06

Technical data

Code	SLI043037WW_PW
Power	10 W
Nominal current	50 mA
Voltage	230 V
Energy consumption	10 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	1100 lm (360°)
Luminous flux	800 lm (360°)
Lamp efficacy	110 lm/W
Luminous intensity	1500 cd
Colour temperature	3000 K
Colour of light	WW
Beam angle	40 °
UGR	<19
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20 / +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
IK	06
Degree of protection (IP)	IP44
Colour	Czarny
Dimension (AxBxC)	75x100 mm
For use	Inside
Assembly method	On the ceiling
Application	Inside
Made in	PRC

Logistics data


Bulk packaging	30 pcs.
Quantity per pallet	720 pcs.
Gross weight (1 pcs.)	0.45 kg



*applies to the LED source used

Related documents



 User manual



 Declaration of Conformity

