

# WLD+40012\_CCT\_2F

SYSTEM SHIFT CCT- GRID M LINING FITURE 330X23X42MM 17W 40deg BLACK CCT SWITCH 5yw 2F




|                    |                             |                           |             |
|--------------------|-----------------------------|---------------------------|-------------|
| Power              | <b>22 W</b>                 | Voltage                   | <b>48 V</b> |
| Colour temperature | <b>2700 / 3300 / 4000 K</b> | Colour of light           | <b>CCT</b>  |
| Beam angle         | <b>35 °</b>                 | Degree of protection (IP) | <b>IP20</b> |

## Technical data


|                              |                      |
|------------------------------|----------------------|
| Code                         | WLD+40012_CCT_2F     |
| Power                        | 22 W                 |
| Nominal current              | 450 mA               |
| Voltage                      | 48 V                 |
| Energy consumption           | 22 kWh/1000h         |
| Frequency                    | DC Hz                |
| Protection class             | III                  |
| Manufacturer of power supply | tuobo                |
| Power factor                 | 1                    |
| Useful luminous flux*        | 2250 lm (360°)       |
| Luminous flux                | 1550 lm (360°)       |
| Lamp efficacy                | 102 lm/W             |
| Luminous intensity           | 4600 cd              |
| Colour temperature           | 2700 / 3300 / 4000 K |
| Colour of light              | CCT                  |
| Beam angle                   | 35 °                 |
| RA                           | 90                   |
| Light source included        | Yes                  |
| Producer of LED diodes       | osram                |
| Uniformity of color SDCM max | 5                    |
| Dimmable                     | No                   |
| Working temperature range    | -20 to +40 °         |
| Warranty                     | 5 years              |
| Lifespan                     | 50000 h              |
| (On/Off)                     | 25000                |
| Housing material             | aluminum             |
| Degree of protection (IP)    | IP20                 |
| Colour                       | Czarny               |
| Dimension (AxBxC)            | 404x23x42 mm         |
| For use                      | Inside               |
| Assembly method              | on track 48V         |
| Application                  | Inside               |
| Made in                      | PRC                  |
| Other                        | 2F ,                 |
| Catalogue number             | WLD+40012_CCT_2F ,   |

## Logistics data



\*applies to the LED source used

## Related documents


 Declaration of Conformity

