

WLD+40004_DALI_DT8

SYSTEM SHIFT DALI TW8 - SPOT S FIXTURE DIRECTIONAL 35x80x120MM 6W 24ST Black DALI TW8 5YW.



Power	12 W	Voltage	48 V
Colour temperature	3000 / 4000 / 6000 K	Colour of light	CCT
Beam angle	150 °	Degree of protection (IP)	IP20

Technical data


Logistics data

Code	WLD+40004_DALI_DT8
Power	12 W
Nominal current	240 mA
Voltage	48 V
Energy consumption	12 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	BOKE
Power factor	1
Useful luminous flux*	1200 lm (360°)
Luminous flux	950 lm (360°)
Lamp efficacy	100 lm/W
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	150 °
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	Czarny
Dimension (AxBxC)	28x400x75 mm
For use	Inside
Assembly method	on track 48V
Application	Inside
Made in	PRC
Other	DT8 ,

*applies to the LED source used

Related documents



 Declaration of Conformity