

# WLD+40011\_DALI\_DT8

SYSTEM SHIFT DALI TW8 - GRID S FIXTURE LINE 220X23X42 12W 40ST Black DALI TW8 5YW.



|                           |                             |                 |               |
|---------------------------|-----------------------------|-----------------|---------------|
| Power                     | <b>12 W</b>                 | Voltage         | <b>48 V</b>   |
| Colour temperature        | <b>2700 / 3300 / 4000 K</b> | Colour of light | <b>CCT</b>    |
| Beam angle                | <b>35 °</b>                 | UGR             | <b>&lt;19</b> |
| Degree of protection (IP) | <b>IP20</b>                 |                 |               |

## Technical data


## Logistics data

|                              |                      |
|------------------------------|----------------------|
| Code                         | WLD+40011_DALI_DT8   |
| Power                        | 12 W                 |
| Nominal current              | 230 mA               |
| Voltage                      | 48 V                 |
| Energy consumption           | 12 kWh/1000h         |
| Frequency                    | DC Hz                |
| Protection class             | III                  |
| Power factor                 | 1                    |
| Useful luminous flux*        | 1200 lm (360°)       |
| Luminous flux                | 750 lm (360°)        |
| Lamp efficacy                | 100 lm/W             |
| Luminous intensity           | 2580 cd              |
| Colour temperature           | 2700 / 3300 / 4000 K |
| Colour of light              | CCT                  |
| Beam angle                   | 35 °                 |
| UGR                          | <19                  |
| RA                           | 90                   |
| Light source included        | Yes                  |
| Uniformity of color SDCM max | 5                    |
| Dimmable                     | DALI                 |
| Working temperature range    | -20 to +40 °         |
| Warranty                     | 5 years              |
| Lifespan                     | 50000 h              |
| (On/Off)                     | 25000                |
| Housing material             | aluminum             |
| Degree of protection (IP)    | IP20                 |
| Colour                       | Czarny               |
| Dimension (AxBxC)            | 220x23x42 mm         |
| For use                      | Inside               |
| Assembly method              | on track 48V         |
| Application                  | Inside               |
| Made in                      | PRC                  |
| Other                        | DALI ,               |

\*applies to the LED source used

## Related documents



 Declaration of Conformity