

WLD+40012_DALI_DT8

SYSTEM SHIFT DALI TW8 - GRID M FIXTURE LINE 330X23X42MM 17W 40ST Black DALI TW8 5YW.



Power	10 W	Voltage	48 V
Colour temperature	3000 / 4000 / 6000 K	Colour of light	CCT
Beam angle	24 °	Degree of protection (IP)	IP20

Technical data


Logistics data

Code	WLD+40012_DALI_DT8
Power	10 W
Nominal current	200 mA
Voltage	48 V
Energy consumption	10 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	BOKE
Power factor	1
Useful luminous flux*	950 lm (360°)
Luminous flux	650 lm (360°)
Lamp efficacy	95 lm/W
Luminous intensity	2100 cd
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	24 °
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	44x157x178 mm
For use	Inside
Assembly method	on track 48V
Application	Inside
Made in	PRC
Other	DT8 ,

*applies to the LED source used

Related documents



 Declaration of Conformity