

# WLD+40013\_DALI\_DT8

SYSTEM SHIFT DALI TW8 - GRID L FIXTURE LINE 440X23X42MM 22W 40ST Black DALI TW8 5YW.



Power	<b>12 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>3000 / 4000 / 6000 K</b>	Colour of light	<b>CCT</b>
Beam angle	<b>25 °</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data

## Logistics data

Code	WLD+40013_DALI_DT8
Power	12 W
Nominal current	230 mA
Voltage	48 V
Energy consumption	12 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	BOKE
Power factor	1
Useful luminous flux*	1150 lm (360°)
Luminous flux	800 lm (360°)
Lamp efficacy	96 lm/W
Luminous intensity	3050 cd
Colour temperature	3000 / 4000 / 6000 K
Colour of light	CCT
Beam angle	25 °
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan (On/Off)	50000 h 25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	40x297 (900mm wire) mm
For use	Inside
Assembly method	on track 48V
Application	Inside
Made in	PRC
Other	DT8 ,

\*applies to the LED source used

## Related documents



 Declaration of Conformity