

# UKCA Declaration of Conformity



www.LEDVANCE.com

Document number: 2024 / 9C1- 4228220-EN-00  
 Manufacturer: LEDVANCE GmbH  
 Address: Parkring 1-5  
 85748 Garching  
 Germany  
 Product type: LED-Lamp  
 Designated Product(s): see list below

We declare herewith under sole responsibility that the designated product(s) is (are) in conformity with the following essential requirements:

| Directive                                 | Designated Standard(s) or Regulation(s)   |
|---|---|
| <b>S.I. 2016 No. 1101 and amendments</b>  | BS EN 62560:2012+A1:2015+A11:2019, BS EN 62493:2015   |
| <b>S.I. 2016 No. 1091</b>                 | BS EN IEC 55015:2019+A11:2020      BS EN IEC 61000-3-2:2019+A1:2021<br>BS EN 61547:2009                      BS EN 61000-3-3:2013+A1:2019+A1:2021 |
| <b>S.I. 2010: No. 2617 and amendments</b> | Commission Regulation (EU) 2019/2020      Commission Delegated Regulation (EU) 2019/2015  |
| <b>S.I. 2012 No. 3032 and amendments</b>  | EN IEC 63000:2018   |

Garching, Mar 6, 2024:

Quality Management

i.V. Yannick Scheyer

Quality Assurance

Name

| Product Codes | Product Description      |
|---------------|--------------------------|
| AC57952       | R39 M3 25 36° 2700K E14  |
| AC57953       | R50 M3 25 36° 2700K E14  |
| AC58870       | R50 M3 25 36° 3000K E14  |
| AC58871       | R50 M3 25 36° 4000K E14  |
| AC57954       | R50 M3 40 36° 2700K E14  |
| AC57955       | R50 M3 40 36° 4000K E14  |
| AC58872       | R50 M3 40 36° 6500K E14  |
| AC58017       | R50 M2+ 60 36° 2700K E14 |
| AC58018       | R50 M2+ 36° 4000K E14    |
| AC58873       | R50 M2+ 36° 6500K E14    |
| AC57956       | R50 M3 60 36° 2700K E14  |

|         |                              |
|---------|------------------------------|
| AC58874 | R50 M3 60 36° 3000K E14      |
| AC58875 | R50 M3 60 36° 4000K E14      |
| AC57976 | R50 M2 60 36° 2700K E14      |
| AC58005 | PAR16 M2+ 35 36° 2700K GU10  |
| AC57999 | PAR16 M2 35 36° 927 GU10     |
| AC58031 | PAR16 M1 35 36° 927 GU10     |
| AC58000 | PAR16 M2 35 36° 930 GU10     |
| AC58032 | PAR16 M1 35 36° 930 GU10     |
| AC58006 | PAR16 M2+ 35 36° 4000K GU10  |
| AC58001 | PAR16 M2 35 36° 940 GU10     |
| AC58879 | PAR16 M2 35 36° 965 GU10     |
| AC58033 | PAR16 M1 35 36° 940 GU10     |
| AC58880 | PAR16 M1 35 36° 965 GU10     |
| AC58025 | PAR16 M1 50 36° 2700K GU10   |
| AC58026 | PAR16 M1 50 36° 3000K GU10   |
| AC58027 | PAR16 M1 50 36° 4000K GU10   |
| AC58881 | PAR16 M1 50 36° 6500K GU10   |
| AC57981 | PAR16 M2 80 36° 2700K GU10   |
| AC58028 | PAR16 M1 80 36° 2700K GU10   |
| AC57982 | PAR16 M2 80 36° 3000K GU10   |
| AC58029 | PAR16 M1 80 36° 3000K GU10   |
| AC57983 | PAR16 M2 80 36° 4000K GU10   |
| AC58882 | PAR16 M2 80 36° 6500K GU10   |
| AC58030 | PAR16 M1 80 36° 4000K GU10   |
| AC58883 | PAR16 M1 80 36° 6500K GU10   |
| AC57984 | PAR16 M2 80 60° 2700K GU10   |
| AC57985 | PAR16 M2 80 60° 3000K GU10   |
| AC57986 | PAR16 M2 80 60° 4000K GU10   |
| AC58884 | PAR16 M2 80 60° 6500K GU10   |
| AC58011 | PAR16 M2+ 80 120° 2700K GU10 |
| AC58012 | PAR16 M2+ 80 120° 4000K GU10 |
| AC57987 | PAR16 M2 80 120° 2700K GU10  |
| AC57988 | PAR16 M2 80 120° 3000K GU10  |
| AC57989 | PAR16 M2 80 120° 4000K GU10  |
| AC58885 | PAR16 M2 80 120° 6500K GU10  |
| AC57969 | PAR16 M3 100 36° 2700K GU10  |
| AC57970 | PAR16 M3 100 36° 3000K GU10  |
| AC57971 | PAR16 M3 100 36° 4000K GU10  |
| AC58886 | PAR16 M3 100 36° 6500K GU10  |
| AC57990 | PAR16 M2 100 36° 2700K GU10  |
| AC57991 | PAR16 M2 100 36° 3000K GU10  |
| AC57992 | PAR16 M2 100 36° 4000K GU10  |
| AC58887 | PAR16 M2 100 36° 6500K GU10  |