

UKCA Declaration of Conformity



www.LEDVANCE.com

Document number: 2025 / 9C1- 4348068-EN-00
 Manufacturer: LEDVANCE GmbH
 Address: Parkring 1-5
 85748 Garching
 Germany
 Product type: Recessed luminaire-Downlight
 Designated Product(s): see list below

Directive ⁹	Designated Standard(s) or Regulation(s)	
S.I. 2016 No. 1101 and amendments	EN IEC 60598-1:2021/A11:2022,	EN IEC 60598-2-2:2024
S.I. 2016 No. 1091 and amendments	BS EN IEC 55015:2019/A11:2020, BS EN IEC 61547:2023,	BS EN IEC 61000-3-2:2019/A1:2021/A2:2024, EN 61000-3-3:2013/A1:2019/A2:2021,
S.I. 2010: No. 2617 and amendments	Commission Regulation (EU) 2019/2020 Commission Delegated Regulation (EU) 2019/2015	
S.I. 2012 No. 3032 and amendments	EN IEC 63000:2018	

Garching, June 10, 2025:

Quality Management

i.V. Yannick Scheyer

Quality Assurance

Chen Shufen

Product Codes	Product Description
AC78744	DL IP44 DN 90 4W 830 440lm WT
AC78745	DL IP44 DN 90 4W 840 460lm WT
AC78746	DL IP44 DN 90 4W 865 460lm WT
AC78747	DL IP44 DN 115 8W 830 880lm WT
AC78748	DL IP44 DN 115 8W 840 920lm WT
AC78749	DL IP44 DN 115 8W 865 920lm WT
AC78750	DL IP44 DN 165 13W 830 1430lm WT
AC78751	DL IP44 DN 165 13W 840 1495lm WT
AC78752	DL IP44 DN 165 13W 865 1495lm WT
AC78753	DL IP44 DN 190 18W 830 1980lm WT
AC78754	DL IP44 DN 190 18W 840 2070lm WT
AC78755	DL IP44 DN 190 18W 865 2070lm WT
AC78756	DL IP44 DN 215 24W 830 2640lm WT
AC78757	DL IP44 DN 215 24W 840 2760lm WT
AC78758	DL IP44 DN 215 24W 865 2760lm WT
AC78759	DL IP44 DN 215 30W 830 3300lm WT
AC78760	DL IP44 DN 215 30W 840 3450lm WT
AC78761	DL IP44 DN 215 30W 865 3450lm WT
AC78762	DL IP44 DN 90 4W 830 440lm BK
AC78763	DL IP44 DN 90 4W 840 460lm BK
AC78764	DL IP44 DN 90 4W 865 460lm BK
AC78765	DL IP44 DN 115 8W 830 880lm BK
AC78766	DL IP44 DN 115 8W 840 920lm BK
AC78767	DL IP44 DN 115 8W 865 920lm BK
AC78768	DL IP44 DN 165 13W 830 1430lm BK
AC78769	DL IP44 DN 165 13W 840 1495lm BK
AC78770	DL IP44 DN 165 13W 865 1495lm BK
AC78771	DL IP44 DN 190 18W 830 1980lm BK
AC78772	DL IP44 DN 190 18W 840 2070lm BK
AC78773	DL IP44 DN 190 18W 865 2070lm BK
AC78774	DL IP44 DN 215 24W 830 2640lm BK
AC78775	DL IP44 DN 215 24W 840 2760lm BK
AC78776	DL IP44 DN 215 24W 865 2760lm BK
AC78777	DL IP44 DN 215 30W 830 3300lm BK
AC78778	DL IP44 DN 215 30W 840 3450lm BK
AC78779	DL IP44 DN 215 30W 865 3450lm BK

#LEDVANCE PLP (V)

#R.YIN #QS

#

#LAB #GCIA Declaration_DL IP44 DN

#2025-06-11 #

#RL-Released

9C1 4348068 - EN -00