

22260007	DATA SHEET	
Valid from: 17.09.2018	AB-B8-M12-8-C	

Description

- Sensor/actuator box
- Connection methods: quick locking without LED pluggable master cable connection and single-occupied slots
- slots: 8



Number of slots:	8
Nominal voltage U _N	120 V
Max. current carrying capacity per path:	2 A
Total current:	1x10 A
Total rated current (for electrical isolation):	2x8 A
Connection type:	pluggable master cable connection
Current carrying capacity per slot:	4 A
Number of poles:	4
Degree of protection:	IP65/IP67/IP69K
Status display:	no
Inflammability class acc. to UL 94:	V0
Contact surface material:	Gold-plated
Material, O-ring:	NBR
Material of the moulding mass:	PUR
Material of threaded sleeve:	Zinc die-cast
Material of threaded sleeve surface:	Nickel-plated
Tightening torque slot sensor/actuator cable:	0.4 Nm
Tightening torque screw plug:	0.4 Nm


Conductor data

Slot/position = Wire colour or connection:	1 / 4 (A) = 1 / 4
--	-------------------


Creator: FELI1/PDP Released: IVSE1/PDP	Document: DB22260007EN Version: 04	Page 1 of 3
---	---------------------------------------	-------------

22260007	DATA SHEET	
Valid from: 17.09.2018	AB-B8-M12-8-C	


Technical drawing



Circuit diagram





Example:




22260007	DATA SHEET	
Valid from: 17.09.2018	AB-B8-M12-8-C	

Schema drawings



Potential U_{N1} and U_{N2} joint.
Potential order:
 $U_{N1} = U_{N2} = \text{slots } 1,2,3,4$



Potential separated. Potential order:
 $U_{N1} = \text{slots } 1, 3 \text{ and}$
 $U_{N2} = \text{slots } 2, 4$

Pin assignment

Slot/ position = Wire color or connection

1 / 4 (A) = WH
 2 / 4 (A) = GN
 3 / 4 (A) = YE
 4 / 4 (A) = GY
 5 / 4 (A) = PK
 6 / 4 (A) = RD
 7 / 4 (A) = BK
 8 / 4 (A) = VT
 1-8 / 1 (+ 120 V) = BN
 1-8 / 3 (0 V) = BU
 1-8 / 5 (PE) = GN/YE

Application range

Automation, industrial machinery and plant engineering

Note

Photographs are not true to scale and do not represent detailed images of the respective products.

Creator: FELI1/PDP Released: IVSE1/PDP	Document: DB22260007EN Version: 04	Page 3 of 3
---	---------------------------------------	-------------