

68100150	<b>DATA SHEET</b>	
Valid from: 19.01.2026	<b>SILVYN® FLEXILOK 90° PG</b>	

SILVYN® FLEXILOK 90° PG is a one-part conduit gland with fast fit for a safety assembling. For the demounting you are using a screwdriver. The gland is suitable for SILVYN® FPAS and can be used in the machine- and plant constructions, control cabinet and building installation.



**Material:** PA66

**Features:** Fast assembling  
Slim design  
Suitable for fine and coarse conduits

**Temperature range:** -40°C up to +120°C

**Colour:** Grey (RAL 7031)  
Black (UV-Resistant)



**Norm reference:** UL FILENUMBER E308201

**Note:** Free of halogen, silicon and cadmium

**Protection class:** IP 66

**Dimension table:**

Part no.	Part name	Thread	Conduit Ø mm	Total length mm	Thread length mm	Outer Ø mm	Inner Ø mm
<b>Black</b>							
6810 0150	SILVYN® FLEXILOK 90° PG	PG 9	16	43	10	21	10,5
6810 0155	SILVYN® FLEXILOK 90° PG	PG 11	16	43	10	21	10,5
6810 0160	SILVYN® FLEXILOK 90° PG	PG 13,5/1	16	44	11	21	14
6810 0170	SILVYN® FLEXILOK 90° PG	PG 13,5/2	21	47	11	26	14
6810 0165	SILVYN® FLEXILOK 90° PG	PG 16/1	16	47	11	26	14
6810 0175	SILVYN® FLEXILOK 90° PG	PG 16/2	21	47	11	26	14
6810 0180	SILVYN® FLEXILOK 90° PG	PG 21	28	57	12	34	19
6810 0185	SILVYN® FLEXILOK 90° PG	PG 29	34	65	12	41	24,5
<b>Grey</b>							
6810 0190	SILVYN® FLEXILOK 90° PG	PG 9	16	43	10	21	10,5
6810 0195	SILVYN® FLEXILOK 90° PG	PG 11	16	43	10	21	10,5
6810 0200	SILVYN® FLEXILOK 90° PG	PG 13,5/1	16	44	11	21	14
6810 0210	SILVYN® FLEXILOK 90° PG	PG 13,5/2	21	47	11	26	14
6810 0205	SILVYN® FLEXILOK 90° PG	PG 16/1	16	47	11	26	14
6810 0215	SILVYN® FLEXILOK 90° PG	PG 16/2	21	47	11	26	14
6810 0220	SILVYN® FLEXILOK 90° PG	PG 21	28	57	12	34	19
6810 0225	SILVYN® FLEXILOK 90° PG	PG 29	34	65	12	41	24,5

For more information please see our current catalogue. Please do not hesitate to contact our laboratory if there are any questions regarding resistance against aggressive agents and special oil.

Creator: PDP Released: PDP	Document: DB68100150EN Version: 02	Page 1 of 1
-------------------------------	---------------------------------------	-------------