

Technical data sheet

Flat angle Signa Base FW 70170

Item number: 6132771



Flat angle as a fitting for changing the direction of the Signa Base device installation trunking.
Cut-concealing flat angle for snapping onto the base.



PC/ABS Polycarbonate/Acrylnitrile-butadiene-styrene

Master data

| | |
|------------------------------------|--|
| Item number | 6132771 |
| Type | BRK FW70170 lgr |
| Description 1 | Flat angle |
| Description 2 | SIGNA BASE 70x170 7035 |
| Manufacturer | OBO |
| Colour | Light grey; RAL 7035 |
| Material | Polycarbonate/Acrylnitrile-butadiene-styrene |
| Smallest sales unit | 1 |
| Unit of quantity | Piece |
| Weight | 25.79 kg |
| Weight unit | kg/100 pc. |
| CO2 Footprint (GWP) Cradle-to-Gate | 1,4681 kg CO2e / 1 Piece |



Technical data sheet

Flat angle Signa Base FW 70170

Item number: 6132771



Dimensions



| | |
|--------|--------|
| Length | 220 mm |
| Width | 220 mm |
| Height | 74 mm |

Technical data

| | |
|-----------------------------------|--------------------------|
| Version for | Hood fitting |
| for duct width | 170 mm |
| for trunking height | 70 mm |
| Halogen-free | yes |
| Cable retaining clip | no |
| Duct connector | no |
| Cover mounting type | Cross-over |
| Mounting perforation in base | no |
| Change of direction | Vertical, rising/falling |
| Protection rating | IP40 |
| Protective film | no |
| Protection rating IK code | IK07. |
| Symmetrical | yes |
| Permitted temperature range, max. | 60 °C |
| Permitted temperature range, min. | -5 °C |
| Angle range, min. | 90 mm |