

# WLD+40008\_DALI\_DT8

SYSTEM SHIFT DALI TW8 - LINE S FIXTURE LINE 304X23X42MM 8W 100ST Black DALI TW8 5YW.



Power	<b>15 W</b>	Voltage	<b>48 V</b>
Colour temperature	<b>3000/4000/6000 K</b>	Colour of light	<b>CCT</b>
Beam angle	<b>100 °</b>	Degree of protection (IP)	<b>IP20</b>

## Technical data


## Logistics data

Code	WLD+40008_DALI_DT8
Power	15 W
Nominal current	300 mA
Voltage	48 V
Energy consumption	15 kWh/1000h
Frequency	DC Hz
Protection class	III
Manufacturer of power supply	BOKE
Power factor	1
Useful luminous flux*	1500 lm (360°)
Luminous flux	750 lm (360°)
Lamp efficacy	50 lm/W
Colour temperature	3000/4000/6000 K
Colour of light	CCT
Beam angle	100 °
RA	90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	DALI
Working temperature range	-20 to +40 °
Warranty	5 years
Lifespan	50000 h
(On/Off)	25000
Housing material	aluminum
Degree of protection (IP)	IP20
Colour	White
Dimension (AxBxC)	602x23x42 mm
For use	Inside
Assembly method	on track 48V
Made in	PRC
Other	DT8 ,

\*applies to the LED source used

## Related documents



 Declaration of Conformity