

# WLD+40006\_DALI\_DT8

SYSTEM SHIFT DALI TW8 - HANGIT FIXTURE HANG IT 40X297 (900MM KABEL) 12W 25ST Black DALI TW8 5YW.



|                    |                         |                           |             |
|--------------------|-------------------------|---------------------------|-------------|
| Power              | <b>5 W</b>              | Voltage                   | <b>48 V</b> |
| Colour temperature | <b>3000/4000/6000 K</b> | Colour of light           | <b>CCT</b>  |
| Beam angle         | <b>165 °</b>            | Degree of protection (IP) | <b>IP20</b> |

## Technical data

## Logistics data

---

|                              |                     |
|------------------------------|---------------------|
| Code                         | WLD+40006_DALI_DT8  |
| Power                        | 5 W                 |
| Nominal current              | 100 mA              |
| Voltage                      | 48 V                |
| Energy consumption           | 5 kWh/1000h         |
| Frequency                    | DC Hz               |
| Protection class             | III                 |
| Manufacturer of power supply | BOKE                |
| Power factor                 | 1                   |
| Useful luminous flux*        | 400 lm (360°)       |
| Luminous flux                | 300 lm (360°)       |
| Lamp efficacy                | 80 lm/W             |
| Colour temperature           | 3000/4000/6000 K    |
| Colour of light              | CCT                 |
| Beam angle                   | 165 °               |
| RA                           | 90                  |
| Light source included        | Yes                 |
| Uniformity of color SDCM max | 5                   |
| Dimmable                     | DALI                |
| Working temperature range    | -20 to +40 °        |
| Warranty                     | 5 years             |
| Lifespan                     | 50000 h             |
| (On/Off)                     | 25000               |
| Housing material             | aluminum            |
| Degree of protection (IP)    | IP20                |
| Colour                       | White               |
| Dimension (AxBxC)            | 100 (815mm wire) mm |
| For use                      | Inside              |
| Assembly method              | on track 48V        |
| Made in                      | PRC                 |
| Other                        | DT8 ,               |

\*applies to the LED source used