



CVE05

CODE		M.U.	CVE05002208000		CVE05002288000		CVE05U12208000		CVE05U12038000
UL Listed			--		--		✓		✓
Rated Voltage		V, ~	230, 1		400, 2	460, 2	230, 1		115, 1
Nominal Frequency		Hz	50	60	50	60	50	60	60
Cooling Capacity	L35L35	W	550	580	500	550	--	580	580
Cooling Capacity	L35L50	W	410	430	380	400	--	430	430
Power Consumption	L35L50	W	320	390	320	390	--	390	390
Current Compsuntion	CE, L35L35	A	1,4	1,6	0,8	0,9	1,4	1,5	--
	UL, L45L55	A	--		--		--	21	4,7
Start-up Current	CE	A	7,5		15		7,5		--
Internal operating temperatures	min/max	°C	+25 / +45		+25 / +45		+25 / +45		+25 / +45
External operating temperatures	min/max	°C	+20 / +55		+20 / +55		+20 / +55		+20 / +55
Internal Circuit Protection Degree	CE	IP	54		54		54		--
	UL	Type	--		--		--	12	12
External Sound Pressure		dB(A)	60		60		60		60
Height (A)		mm	642		642		642		642
Width (B)		mm	314,5		314,5		314,5		314,5
Depth (C)		mm	221		221		221		221
Weight		kg	17		17		23		23